



SAFETY DATA SHEET R290

Code: TR290

Material safety data sheet according regulation (EU) 2015/830
Version 4 – Date: 13th May, 2019

From protected position, cool endangered containers with water spray jet.
Do not discharge contaminated water into drains.
If possible, stop flow of the product.
If possible, use water spray to knock down the fumes.
Explosive re-ignition may occur, turn off all the other fire.
Move containers from fire area if this can be done without risk.

Protective equipment Firefighters must use standard protective equipment including SCBA.
Avoid contact with eyes and skin. Do not breathe the fumes.

Other information

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
For more information, see section 10.

6. Accidental release measure

6.1 Personal precautions, protective equipment and emergency procedures

Immediately contact emergency personnel.
Immediately evacuate personnel to safe areas. Unprotected persons must be kept away.
Wear personal protective equipment refer to section 8 "Exposure controls/personal protection".
Remove all sources of ignition.
Avoid contact with skin (possible frostbite).
Ventilate the area/local. In case of insufficient ventilation, wear self-contained breathing apparatus.

6.2 Environmental precautions

Do not allow product to spread into the environment.
Avoid spillage and prevent possible losses.

6.3 Methods and material for containment and cleaning up

Ventilate / aerate the area or local.

6.4 Reference to other sections

For more information, see section 8 and 13.

7. Handling and storage

7.1 Precautions for safe handling

Technical measures	Use only properly specified equipment that is suitable for this product, its supply pressure and temperature. In case of doubt, refer to supplier's handling instructions. Only experienced and properly instructed persons should handle gases under pressure. Service technician must check regularly your entire gas system to ensure that it is leak-free.
Safe handling	The substance must be handled in accordance with good industrial hygiene and safety procedures. Refer to supplier's / manufacturer's handling instructions. Handle and open container with care. Caution when opening, pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50° C (122 °F). Do not spray on a naked flame or any incandescent material. Do not use in area without adequate ventilation. Protect containers from physical damage; do not drag, roll, slide or drop. Do not pierce or burn, even after use. Leave valve protection caps in place until the container is ready for use. Close container valve after each use and when empty, even if still connected to equipment. Do not remove or deface labels provided by the supplier for the identification of the container contents.
Industrial hygiene	Ensure adequate ventilation of the working area. Do not drink, eat or smoke in the working area.

Material safety data sheet according regulation (EU) 2015/830
Version 4 – Date: 13th May, 2019

7.2 Conditions for safe storage, including any incompatibility

Requirements for storage areas and containers

Keep containers tightly closed in a dry, cool and well-ventilated place, away from any ignition or heat sources. Store in original container. Container valves or caps should be in place.

Incompatible materials

Avoid storage with oxidizing products, acids and, in general, with chemicals.
Avoid storage with tools or equipment that may cause sparks.

7.3 Specific end use(s)

For professional and industrial use only.

8. Exposure controls/personal protection

8.1 Control parameters

OEL (Occupational Exposure Limit): No data available.

Components	CAS No.	TLV-TWA	Control parameters	Font	Year
Propane	74-98-6	8 h	2500 ppm 4300 mg/m ³	AGCIH	2010

DNEL and **DMEL** = the substance have no harmful effect on human health.

PNEC = the substance have no harmful effect on the environmental.

8.2 Exposure controls

Ensure adequate ventilation. In case of insufficient ventilation, wear self-contained breathing apparatus.

Wash the hands before and after using the gas. Do not smoke.

Personal protective equipment must comply with EU directives: respiratory protective equipment EN 136, 140, 149; eye protection (protective goggles or safety glasses) EN 166; skin protection EN 340, 463, 468, 943-1, 943-2; hands protection (protective gloves) EN374, safety boots EN ISO 20345.

8.2.2 Individual protection measures, such as personal protective equipment

- a) Eye/face protection** Safety glasses with side-shields (according to directive EN 166).
- b) Skin protection**
 - i) Hand protection It is recommended to use protective gloves against cold (EN 511).
The penetration time of the gloves must be greater than the period of expected use. Gloves should be replaced immediately if they show signs of wear or deterioration.
 - ii) Other Evaluate the need for flame resistant workwear.
EN ISO 14116 Protective clothing - Protection against heat and flame - Limited flame spread materials.
EN ISO 1149-5 Protective clothing – Electrostatic properties.
Wear safety shoes while handling containers.
EN ISO 20345 Personal protective equipment - Safety shoes.
Apron or protective clothing are not necessary.
- c) Respiratory protection** The vapours are heavier than air and can cause asphyxia caused to an reduction of oxygen level. In case of insufficient ventilation, wear self-contained breathing apparatus (EN 133).



8.2.3. Environmental exposure controls

Handling in accordance with good industrial hygiene and safety practice.

Prevent spillage or leakage of the product in watercourse or sewers (explosion danger). Avoid air emissions.

For more information, see section 7.



SAFETY DATA SHEET R290

Code: TR290

Material safety data sheet according regulation (EU) 2015/830
Version 4 – Date: 13th May, 2019

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Appearance	Liquefied gas; under pressure
Colour	Colourless
b) Odour	Ethereal
c) Odour threshold	Odour threshold is subjective and is inadequate to warn of over exposure.
d) pH	n.a.
e) Melting point	- 189,7 °C
f) Initial boiling point	- 42 °C
g) Flash point	- 104 °C
h) Evaporation rate	Not applicable to gas and mixtures
i) Upper/lower flammability	n.d.a.
j) Vapour pressure	1.370 Pa max
k) Vapour density	0,507 Kg/l @ 15 °C
n) Solubility (water)	n.d.a.
o) Partition coefficient: n-Octanol/water	n.d.a.
p) Auto-ignition temperature	> 460 °C
q) Decomposition temperature	n.d.a.
r) Viscosity	n.d.a.
s) Explosive properties	n.d.a.
t) Oxidising properties	Not oxidising according with EU criteria

9.2 Other information

Explosive limits	2,4 – 9,5% Vol.
Solubilities (other substances)	Soluble in ether, ethanol and chloroform
Conducibility	n.d.a.
Miscibility	n.d.a.
VOC contents	≥ 90 % (EU,CH, USA)

10. Stability and reactivity

10.1 Reactivity

Stable under normal handling and storage conditions.

10.2 Chemical stability

Stable under normal handling and storage conditions.

10.3 Possibility of hazardous reactions

May react violently with oxidants.

Can form explosive mixture with air.

10.4 Conditions to avoid

Contains gas under pressure, may explode if heated.

Protect from sunlight and do not expose to temperatures exceeding 50 °C.

Keep away from heat, sparks, open flame or other sources of ignition. Do not smoke.

Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

10.5 Incompatible materials

Air, oxidizing agents.

10.6 Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

In case of combustion, toxic compositions, may be formed: carbon monoxide (CO) and carbon dioxide (CO₂).



SAFETY DATA SHEET R290

Code: TR290

Material safety data sheet according regulation (EU) 2015/830
Version 4 – Date: 13th May, 2019

11. Toxicological information

11.1 Information on toxicological effects

a) Acute toxicity	No known effect for this substance
Inhalation	CL50: > 800 000 ppm Exposure time: 15 minutes Animal species: Rat
Oral	n.d.a.
Skin	n.d.a.
b) Skin corrosion/Skin irritation	Compressed gases, may cause frostbite on contact with skin.
c) Serious eye damage/irritation	Compressed gases, may cause frostbite on contact with skin.
d) Respiratory sensitisation	n.d.a.
e) Germ cell mutagenicity	n.d.a.
f) Carcinogenicity	n.d.a.
g) STOT-single exposure	n.d.a.
h) STOT-repeated exposure	n.d.a.
j) Aspiration hazard	n.d.a.

Other information

High concentrations may cause drowsiness, headache and dizziness. If the amount of oxygen in the air drops below 17% may cause unconsciousness, asphyxia and / or CNS depression.

Contact with compressed gas may cause frostbite and serious ocular injury.

12. Ecological information

12.1 Toxicity

Fish	CL50: 49,90 mg/l Exposure time: 96 h
Daphnia magna	CL50: 27,10 mg/l Exposure time: 48 h
Algae	CL50: 11,90 mg/l Exposure time: 72 h

12.2 Persistence and degradability

The substance will be readily biodegradable and it is not expected to persist in the environment.

12.3 Bioaccumulative potential

The substance are not considered to be persistent in the environment due to its low log Kow (log Kow < 4).

12.4 Mobility in soil

Because of its high volatility, the product is unlikely to cause ground or water.

12.5 Results of PBT and vPvB assessment

Not classified as PBT or vPvB.

12.6 Other adverse effects

Ozone Depletion Potential	ODP (R-11=1) = 0
Global Warming Potential	GWP (CO2=1) = 3

Material safety data sheet according regulation (EU) 2015/830
Version 4 – Date: 13th May, 2019

13. Disposal consideration

13.1 Waste treatment methods

Product Take all necessary measures to prevent the production of residuals, value the possible methods of regeneration or recycling. Dispose in accordance with local, state, and federal regulations. Do not discharge into drains or environment.

Packaging Reuse and recycle the packaging after its reclaim. Dispose of non-reusable packaging in accordance with local, state, and federal regulations.

European Waste Code (EWC)

Product 16 05 04: Gases in pressure containers (including halons) containing dangerous substances.

Packaging 15 01 11: metallic packaging containing a hazardous solid porous matrix (for example asbestos), including empty pressure containers.

Additional information

Waste directives and regulations: Directive 2006/12/CE, Directive 91/689/CE, Regulation (EC) no. 1013/2006.
Dispose of waste product in compliance with EC, state and/or local regulations.
For more information, see section 8.

14. Transport information

14.1 UN Number UN 1978

14.2 UN proper shipping name Propane

Hazard labels

ADR/RID, IMDG, IATA/ICAO



2.1 Flammable gas

Transport by road (ADR) / Transport by rail (RID)

14.3 Transport hazard class(es) <i>Classification code</i> <i>Kemler code</i>	2 2F 23
14.4 Packing group <i>Packing instruction</i>	n.a. P200
14.5 Environmental hazards	No
Additional information <i>Tunnel restriction code of total load</i>	B/D: Passage forbidden through tunnels of category B & D.

Transport by air (IATA/ICAO)

14.3 Transport hazard class(es) <i>Class/Division</i>	2 2.1
14.4 Packing group <i>Passengers and cargo flights</i> <i>Only cargo flights</i>	n.a. Forbidden 200
14.5 Environmental hazards	No

Transport by sea (IMDG)

14.3 Transport hazard class(es) <i>Class/Division</i> <i>Emergency Schedule (EmS)</i>	2 2.1 F-C, S-V
14.4 Packing group <i>Packing instruction</i>	n.a. P200
14.5 Environmental hazards	No



SAFETY DATA SHEET R290

Code: TR290

Material safety data sheet according regulation (EU) 2015/830
Version 4 – Date: 13th May, 2019

14.6 Special precautions for user

Avoid transport on vehicles where the load space is not separated from the driver's compartment.
Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.
Ensure that containers are firmly secured.
Ensure there is adequate ventilation.

14.7 Transport in bulk according in Annex II of MarPol and the IBC Code

Not applicable.

15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depletion Potential ODP (R-11=1) = 0
Global Warming Potential GWP (CO2=1) = 3

Additional regulations/legislations

Regulation (EU) No. 517/2014
Directive Seveso 96/82/EC: Not included

15.2 Chemical safety assessment

A Chemical Safety Assessment (CSA) has been made for this product.

16. Other information

This Material Safety Data Sheet has been made according European Directive in force.

Text of H and P phrases in section 2 and 3

H220: Extremely flammable gas
H280: Contains gas under pressure; may explode if heated
P210: Keep away from heat/sparks/open flames/hot surfaces – No smoking
P377: Leaking gas fire: Do not extinguish unless leak can be stopped safely
P381: Eliminate all ignition sources if safe to do so
P403: Store in a well ventilated place

Text of R and S phrases in section 2

R12: Extremely flammable
S2: Keep out of the reach of children
S9: Keep container in a well-ventilated place
S16: Keep away from sources of ignition - No smoking

Text of "Security code" in section 3; under Regulation (EC) 1272/2008 (CLP) and Classification n. 67/548/EEC

Flam. Gas 1 Flammable gas Category 1
Press. Gas (Liq.) Pressurized gas : Liquefied gas
F+ ; R12 Extremely Flammable

History	Revision date: 05/2019	Version 3	Version 2	Version 1
		Date: 11/2015	Date: 05/2015	Date: 03/2011

b) Abbreviations and acronyms

ADR	Accord Dangerous Route
CAS	Chemical Abstracts Service
CE / EC	European Community
CLP	Classification, Labelling and Packaging
CSA	Chemical Safety Assessment
DNEL	Derived No Effect Level
DMEL	Derived Minimum Effect Level
EC50	Effective Concentration 50%



SAFETY DATA SHEET R290
Code: TR290

Material safety data sheet according regulation (EU) 2015/830
Version 4 – Date: 13th May, 2019

EmS	Emergency Schedule
EWS	European Waste System
GHS	Globally Harmonized System
GWP	Global Warming Potential
HCFC	Hydro-Chloro-Fluoro-Carbons
HFC	Hydro-Fluoro-Carbons
IATA	International Air Transport Association
IBC Code	International Bulk Chemical code
ICAO	International Civil Aviation Organization
IMDG code	International Maritime Dangerous Goods code
LC50	Lethal Concentration 50%
Log Kow	Logarithm Partition coefficient N-octanol /Water
n.a.	not applicable
n.d.a.	no data available
ODP	Ozone Depletion Potential
OEL	Occupational Exposure Limit
PBT	Persistent, Bioaccumulative, Toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Rail International Dangerous Goods
STOT-RE	Specific Target Effect Concentration (Repeated Exposure)
STOT-SE	Specific Target Effect Concentration (Single Exposure)
TLV	Threshold Limit Value
TWA	Time Weighted Average
UE / EU	European Union
VOC	Volatile Organic Compounds
vPvB	very Persistent very Bioaccumulative

Notice of liability

This information should not constitute a guarantee for any specific product properties. This information are only a guidance for safe handling, use, processing, storage, transportation, disposal and release and are not to be considered a warranty or a quality specification.

The information contained in this safety data sheet are based on our current knowledge and EU and national laws; they describe the product only with regard to safety requirements. The conditions of the user are beyond our knowledge and control. The product should not be used for purpose other than those specified. It is always the responsibility of the user to take all the necessary measures to comply with the requirements of current legislation. The information contained in this form should not considered as a guarantee of its properties.
